

Heavy Duty Cylindrical

MIL-DTL-5015, 3100 & 3400



LEX
Connector Solutions



Lex™3 offers a wide variety of 5015 power connectors. These connectors are ideal for use in highly ruggedized applications, where power/signal has to be transmitted in an environment of extremely low or high temperatures, with high vibration and shock also present. Apart from providing mechanical protection to the contacts, the connectors offer the advantage of being light weight and easy to handle, which facilitates ease of mating/unmating.

- **HOUSING:** Aluminium alloy to provide high mechanical strength while ensuring light weight.
- **SURFACE FINISH:** Standard finish is olive drab chromate over cadmium, for corrosion resistance and use in extreme operating condition. ROHS finishes available. Bright Nickel Plated, Electroless Nickel, Zinc Alloy
- **INSULATOR:** Standard insulator material is Polychloroprene, which provides high degree of insulation resistance, dielectric strength, ability to withstand shock, impact and vibration. Options include Silicon, Viton, and a flame-retardant halogen-free compound which has properties of low smoke and non-toxicity.

- **CONTACTS:** Copper base alloy - silver (or gold) plated, available in a range of current ratings from 10 amps to 150 amps. These offer excellent conductivity under severe service conditions with minimum loss or discontinuity of current even in dynamic applications. Both solder and crimp terminations are available.
- **Large array of over 100 insert arrangements** in 13 shell sizes for power, signal, and combinations of power and signal pin configurations are available for a variety of applications.
- **Temperature:** Operating temperature from -40°C to $+125$ (3100) and -40°C to $+200$ (3400).



PART NUMBER						
Mil Spec	1	2	3	4	5	6
MS31	00	E	14-3	P	Y	NI

ACCESSORIES

CONNECTOR CAP & CHAIN - OVERMOLDED CABLE ASSEMBLIES

1. MS Number –

MS3100	Wall Mount Receptacle
MS3101	Cable Connecting Receptacle
MS3102	Box Mount Receptacle
MS3106	Straight Plug
MS3108	Cable Connector Right Angle

For commercial callout, replace MS with TM

2. Class –

E	Environmental Resistance with Cable Clamp
F	Environmental Resistance with Cable Clamp and O Ring
R	Environmental resistant for Receptacle

3. Shell Size and Insert Arrangement–

4. Contact Type –

P	Pin
S	Socket

5. Alternate Insert Position

W,X,Y, or Z	
None	= Normal

6. Finish options

NI	Bright Nickel Plated
ENI	Electroless Nickel
ZCG	Cadmium Free Zinc Alloy (Green)

Omit for Std. Cadmium Olive Drab

7. Accessories

C & C	Cap and Chain Assembly
DC	Dust Cap



LEX CONNECTORS // Smart power, anywhere.™

#300 15751 SW 41 Street
Davie, FL 33331

Phone: 954-888-1024
Email: info@lexconnectors.com
www.lexconnectors.com

CAGE Code: 00Y95, 7GFW9, 6ZKC3
GSA Contract: GS-07F-0296N
NAICS Codes: 334419, 335311, 335313, 335314,
335931, 335999

© 2017 All Rights Reserved.